

AMENDMENTS TO THE CLAIMS

1. (Currently Amended) An apparatus comprising:
an elongated member having dimensions suitable for insertion into a body ~~and~~, a distal portion suitable for insertion into tissue, a distal opening, and a lumen in communication with the opening to allow a substance to be delivered through the lumen and out of the opening;
a thermally conductive heating element coupled to the distal portion of the elongate member, the heating element comprising material whose electrical resistance changes in response to a change in temperature; and
an interface to a balanced circuit having the heating element and a variable resistor as resistive circuit elements, wherein the balanced circuit measures a first differential resistance between the heating element and the variable resistor in response to a first condition and a second differential resistance in response to a second condition in circuitry to indicate a change of conditions related to a distance of penetration of the thermally conductive heating element into a tissue.
2. (Original) The apparatus of Claim 1, wherein the elongate member comprises a needle.
3. (Original) The apparatus of Claim 2, wherein the needle has an outer diameter between 0.009 inches and 0.134 inches.
4. (Original) The apparatus of Claim 2, wherein the needle comprises a material of at least one of stainless steel and ceramic.
5. (Original) The apparatus of Claim 1, wherein the elongate member is a rod.
6. (Original) The apparatus of Claim 1, wherein the heating element comprises at least one of a wire, a film, and a thermistor material.

7. (Previously Presented) The apparatus of Claim 1, wherein the heating element has a length which is approximately equal to or less than the thickness of a tissue in to which at least a portion of the elongate member is to be inserted.

8. (Original) The apparatus of Claim 7, wherein the length of the heating element is between 0.010 inches and 0.400 inches.

9. (Previously Amended) The apparatus of Claim 1, wherein the interface is an anemometry circuitry interface comprising:

a first electrically conductive lead electrically coupled to a first end of the heating element; and

a second electrically conductive lead electrically coupled to a second end of the heating element.

10. (Currently Amended) The apparatus of Claim 1, wherein a portion of the elongate member comprises an electrically conductive material and wherein the ~~anemometry circuitry~~ interface comprises:

an electrically conductive lead electrically coupled to a first end of the heating element, and

the elongated member electrically coupled to a second end of the heating element.

11. (Currently Amended) An apparatus comprising:

a needle having dimensions suitable for insertion into a body, and having a distal end capable of puncturing skin;

a thermally conductive heating element coupled to a portion of the needle, the heating element comprising material whose electrical resistance changes in response to a change in temperature; and

an interface to electrically coupled an anemometry circuitry ~~electrically coupled~~ to the heating element, wherein the circuitry comprises a balanced circuit having the heating element and a variable resistor as resistive circuit elements.

12. (Original) The apparatus of Claim 11, wherein the needle has an outer diameter between 0.009 inches and 0.134 inches.

13. (Original) The apparatus of Claim 11, wherein the needle comprises a material of at least one of stainless steel and ceramic.

14. (Currently Amended) The apparatus of Claim 11, further comprising anemometry circuitry electrically coupled to the heating element wherein the circuitry comprises a balanced circuit having a heating element and a variable resistor as resistive circuit elements, wherein the heating element comprises at least one of a wire, a film, and a thermistor material.

15. (Previously Presented) The apparatus of Claim 11, wherein the heating element has a length which is approximately equal to or less than the thickness of a tissue in to which at least a portion of the needle is to be inserted.

16. (Original) The apparatus of Claim 15, wherein the length of the heating element is between 0.010 inches and 0.400 inches.

17. (Currently Amended) The apparatus of Claim ~~11~~14, wherein the anemometry circuitry is electrically coupled to a first end of the heating element by a first electrically conductive lead and is electrically coupled to a second end of the heating element by a second electrically conductive lead.

18. (Currently Amended) The apparatus of Claim ~~11~~14, wherein a portion of the elongate member comprises an electrically conductive material and wherein the anemometry circuitry is electrically coupled to a first end of the heating element by an electrically conductive lead and is electrically coupled to a second end of the heating element by the elongate member.

19. (Currently Amended) The apparatus of Claim ~~11~~14, wherein the anemometry circuitry comprises:

a circuit having the heating element and a variable resistor as resistive circuit elements; and

an amplifier electrically coupled to the circuit
to sense the difference in voltage drop across the heating element and the variable resistor caused by the difference between a first resistance of the heating element and a resistance of the variable resistor,
to amplify the voltage difference, and
to input the amplified voltage difference back to the circuit to cause a modification of a temperature of the heating element such that the heating element assumes a second resistance.

20. (Previously Presented) The apparatus of Claim 19, further comprising an additional heating element wherein the heating element and the additional heating element are coupled along a length of the elongate member, and further comprising:

anemometry circuitry separately coupled to each of the heating element and the additional heating element such that the heat dissipation characteristics measured by the plurality of anemometry circuits can be used to determine at least one of injection depth and tissue type.

21-25. Canceled.

26. (Previously Presented) The apparatus of Claim 11 wherein the needle has dimensions suitable for insertion into a tissue of the body and the balanced circuit is configured to measure a distance of penetration of the thermally conductive heating element into the tissue.